


New  
**BK70AA**  
AA size (HR15/49)

Old  
(HHR70AA)

Standard type



**■ Dimensions (with tube)**




**■ Specifications**

Diameter	14.5 +0 / -0.7 mm
Height	49.0 +0 / -1.5 mm
Approximate Weight	18 g



Nominal Voltage		1.2 V	
Discharge <sup>*1</sup> Capacity	Average <sup>*2</sup>	780 mAh	
	Rated (min.)	700 mAh	
Approx. Internal impedance at 1000Hz at charged state.		25 mΩ	
Charge	Standard	70 mA X 16 hrs.	
	Rapid <sup>*3</sup>	700 mA X 1.2 hrs.	
Ambient Temperature	Charge	Standard	0 °C to 45 °C
		Rapid	0 °C to 40 °C
	Discharge		-10 °C to 65 °C
	Storage	<1 year	-20 °C to 35 °C
<6 months		-20 °C to 45 °C	
<1 month		-20 °C to 55 °C	
<1 week		-20 °C to 65 °C	

\*1 After charging at 0.1 It for 16 hours, discharging at 0.2 It.  
\*2 For reference only.  
\*3 Need specially designed control system. Please contact Panasonic for details.

**■ Typical charge characteristics**



**■ Typical discharge characteristics**



Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic when determining charge/discharge specs, warning label contents and unit design.

\*The data in this document are for descriptive purposes only and are not intended to make or imply any guarantee or warranty.